

7V7
7W7



7V7

SHARP-CUTOFF PENTODE

Plate Current.	10	10	ma
Grid-No.2 Current. . .	3.9	3.9	ma
Plate Resistance . . .	0.3	0.3	megohm
Transconductance . . .	5800	5800	μ mhos
Grid-No.1 Bias (Approx.) for plate current of 10 μ a.	-8	-16	volts
* Condition I with fixed grid-No.2 supply gives a sharp-cutoff characteristic.			
** Condition II with series grid-No.2 resistor gives an extended-cutoff characteristic.			
# When grid-No.2 supply voltage in excess of 150 volts is used, a series grid-No.2 resistor must be used to limit grid-No.2 voltage to 150 volts when the plate current is at its normal value of 10 ma.			

7W7

SHARP-CUTOFF PENTODE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage.	6.3 [□]	ac or dc volts
Current.	0.45 ^{□□}	amp

Direct Interelectrode Capacitances:[○]


Grid No.1 to Plate . .	0.0025 max.	μ mf
Input.	9.5	μ mf
Output	7	μ mf

[○] With external shield connected to cathode.

Mechanical:

Mounting Position.	Any
Maximum Overall Length	2-25/32"
Maximum Seated Length.	2-1/4"
Maximum Diameter	1-3/16"
Bulb	T-9
Base	Lock-in 8-Pin
Basing Designation for BOTTOM VIEW	8BJ

Pin 1-Heater
Pin 2-Plate
Pin 3-Grid No.2
Pin 4-Cathode
Pin 5-Grid No.3,
Internal
Shield



Pin 6-Grid No.1
Pin 7-Cathode
Pin 8-Heater
Plug - Base
Shell

Maximum Ratings, Typical Operation, and Characteristics
are the same as for Type 7V7

[□] Nominal voltage = 7.0 volts.

^{□□} Nominal current = 0.48 ampere.

JUNE 15, 1948

TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

DATA